

**EVERBUILD ULTRA HARD FLOOR VARNISH**

Colour	Product Code	Pack Size	Box Qty
Gloss	FLOORVGL07	750ml	6
	FLOORVGL2	2.5ltr	2

**Product Description**

Everbuild Ultra Hard Floor Varnish is a clear quick drying varnish ideal for use on most common types of wooden floors including hardwood, softwood, hardboard, chipboard and composite wooden boards.

Everbuild Ultra Hard Floor Varnish has been specifically developed to provide an ultra-hard scratch resistant natural finish to most interior wooden floors. Suitable for use in kitchens, bathrooms, lounge, dining areas or where heavy foot traffic would be expected.

**Benefits**

- Low Solvent Formula
- Touch dry in 30 minutes.
- Protects wood against scratches and spills.
- Clear finish, no discoloration.

**Surface Preparation**

On unvarnished floors ensure wood is clean, dry and free from dirt or dust by wiping with a soft cloth and white spirit. Any existing coatings must be removed prior to application with a suitable sander using 120 grade abrasive paper. A suitable dust mask should be worn while sanding. Allow any dust to settle then vacuum the floor to remove any dust or debris. Fill in any holes or surface imperfections using Everbuild Multi-Purpose Wood Filler.


Existing varnished floors should be thoroughly sanded using 120 grade abrasive paper to provide a key for Everbuild Ultra Hard Varnish to be applied. Floors should be vacuumed, wiped down with white spirit and allowed to dry. Any existing varnish in poor condition should be completely removed prior to application.

**Application**

Stir product well before use and periodically during application. Brush apply Everbuild Ultra Hard Floor Varnish following the direction of the wood grain. Apply a minimum of 3 coats allowing 1 hour between coats. Lightly sand the surface before applying the final coat. Always apply the varnish to a wet edge working systematically across the surface keeping the wet edge together as much as possible to avoid overlap.

Ultra Hard Floor Varnish can be walked on after approximately 8 hours depending on ambient temperature and conditions. Allow 72 hours before subjecting to heavy foot traffic. Do not cover with carpets or rugs for at least 7 days. Protect from water for 5 days. Clean brushes thoroughly after use with warm soapy water.

### Test Data



### Limitations

Do not use externally.

Always test a small inconspicuous area prior to full application.

Do not use below 10°C.

Do not use in areas subject to prolonged water contact.

Do not use on laminate floors.

It is the user's responsibility to determine suitability for use. If in doubt contact Technical Services for advice.

### Coverage Guide

Up to 16 square metres per litre. Coverage will vary depending on the absorbency of the wood.

### Health & Safety

See MSDS for full list of hazards.

### Storage

Store in cool dry conditions between + 5 and +25°C. Storage outside these conditions will dramatically reduce shelf life. PROTECT FROM FROST.

### Shelf Life

2 years from date of manufacture when stored as directed.

*The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.*